

RAIS Visio 3 INSET SPECIFICATION SHEET

Dimensions (W-D-H)

External dimensions (W-D-H) in mm: 759 - 564 - 1.537

Combustion chamber inner dimensions (W-D-H) in mm: 533 - 333 - 466

Installation dimensions (W-D-H) in mm: 685 - 490 - 432

Outer frame dimensions (W-D-H) in mm: 854 - 557 - 444

Flue outlet (diameter): 200

Output

Heating (at -20°C) in m2: 75 - 120

Efficiency in %: 80%

Particulates in g/kg: 6,5

Dust: 5 mg/ Nm³

Weight in kg: 260

Distance to flammable material

To side wall in mm: 300

To back wall in mm: 150

To the ceiling in mm: 698

To the side in mm: 200

To the floor in mm: 385

In front of the floor in mm: 300

To furniture: 1200

Specifications

Glass door with black edge: STANDARD

Glass door with rustproof edge: ACCESSORY

Cover frame, black: ACCESSORY

Cover frame, rustproof: ACCESSORY

Specifications

Measurement (W-D-H)

Stove outer measurements 759 - 564 - 1537 mm

Firebox, interior measurements 533 - 333 - 466 mm

Minimum fireplace opening 685 - 443 - 432 mm

Frame, outer measurements (W-H) 854 - 557 mm - 444 mm

Flue exit (diameter) Ø 200 mm

WEIGHT

Weight 243 kg

1246554 - Visio 3

